

Outrunner Cable System

OutRunner - Quick Connect Cable System

The new quick connect cable system, OutRunner, from ALTINEX was designed with the rental and staging industry in mind. This unique cable allows users to quickly switch between connector types. Switch from BNC connector to S-video or 15-pin HD connector by simply unplugging the short patch cable from your regular cable run. The standard lengths offered are 15, 25, 35, 75, 100, and 150ft. Based on the high quality coax cable CB4200MR from ALTINEX, both ends of the cable are terminated with 7-pin XLR connectors to assure that a high quality signal is maintained at all times. Extender cables are also available to make cable longer length. The OutRunner cables should be treated the same way as any coax cables on the cable length limitation

- * Quick and easy to connect
- * Reliable, high quality 7-pin XLR connectors
- * High quality coax cable
- * Strong protective jacket
- * Many standard and custom-length cables
- * Over 10 different Break Away adapters



7pin XLR Male to 7pin XLR Male

Part#	Length
CB701-451	2ft [0.61m]
CB701-121	15ft [4.57m]
CB701-122	25ft [7.62m]
CB701-123	35ft [10.67m]
CB701-124	50ft [15.24m]
CB701-125	75ft [22.86m]
CB701-126	100ft [30.48m]
CB701-127	150ft [45.72m]

Short Patch Cables

End Cable:	Part Number	Length
2RCA Male+4pin Mini-Din Male	CB701-309	3ft [0.91m]
3RCA Male+4pin Mini-Din Male	CB701-301	3ft [0.91m]
3RCA Male for YPbPr	CB701-302	3ft [0.91m]
3RCA Male for Video+Audio	CB701-305	3ft [0.91m]
4RCA Male	CB701-303	3ft [0.91m]
5RCA Male	CB701-304	3ft [0.91m]
15pin HD Male	CB701-306	3ft [0.91m]
15pin HD Female	CB701-307	3ft [0.91m]
5BNC Male	CB701-308	3ft [0.91m]

Attenuation

10 MHz	1.6 dB/100ft
50 MHz	4.0 dB/100ft
100 MHz	6.1 dB/100ft
200 MHz	9.8 dB/100ft
300 MHz	13.0 dB/100ft
400 MHz	15.9 dB/100ft
1000 MHz	30.4 dB/100ft



ALTINEX[®]

**SIGNAL
MANAGEMENT
SOLUTIONS**[™]